

Series 1028/G

- Test probe for cable harness testing
- Screwable - threaded design
- Screwing tools available

Mechanical Data

Center	2.54 mm/100 mil
Full Travel	5.30 mm
Working Travel	4.00 mm
Pre-loaded Spring Force	0.30/ 0.40/ 0.60/ 0.80/ 1.10/ 1.30 N
Spring Force at Working Travel	0.70/ 1.00/ 1.50/ 2.25/ 3.00/ 5.00 N

Electrical Data

Max. Current Rating	5.0...8.0 A
Typical Continuity Resistance	<= 25 mOhm






Materials






Barrel	Brass, gold plated
Spring	Spring Steel, gold plated
Plunger	Steel
Receptacle	Brass, gold plated






Recommended Diameter of Drill





H1021/GR	
HP 2361.1 (Trolitax)	2.00 mm
HGW 2372	2.03 mm

Tip style - Diameter - Plating

				
A	B	BST	C	CSM
1.50 Au 1.80 Ni	1.30 Rh	0.80 Au	1.40 Au 1.80 Rh 2.50 Rh 3.50 Rh	1.00/2.00 Au/HTK

				
D	D1	EB	F	G
1.40 Au	0.65 Ni 0.80 Ni	1.80 Au	1.30 Ni	1.30 Ni 1.50 Rh

				
H	H	K	M6	Q
1.30 Au	1.40 Au 1.80 Au	1.30 Au 1.75 Ni	2.00 Rh	1.30 Au

			
Q	Q5	Q8	V
1.80 Au 2.00 Au	1.30 Ni	2.30 Ni	1.30 Ni

How to Order

1028/	G	-	A	-	1.5	N	-	Ni	-	1.8
1	2	3	4	5	6					
1. Series 2. Threaded Design 3. Tip Style										
4. Spring Force 5. Tip Plating 6. Tip Diameter										

Series 1028/G

